



Specifications :

Flow rate	5L/MIN
Concentration	93+3%
Power	390W
Sound Level	<45db
Outlet Pressure	40-70KPa
Net Weight	13.9 kg
Gross Weight	15 kg
Warranty	3 years

- Folding 3.5" LCD Screen
- Power failure Alarm
- Over-heat Alarm
- Low Purity Alarm
- Voltage Alarm
- Low Pressure/High Pressure alarm
- Maintenance prompt
- Power On self test and LVD
- Oxygen Purity percentage display
- Designed for 24 hour working

5 litres

Product Code : MAOXY05
(AR-5-N)

- Flow rate 1-5 LPM, with an increment of 0.5 LPM
- High / Low voltage Alarm Sensors
- PSA (Pressure Swing Adsorption) Technology
- Inbuilt Nebulizer and Timer (10 MIN to 5 HOURS)
- Alarms for Low Oxygen purity, Low pressure, Power Outage and defective information is displayed on the screen
- Intelligent self-diagnosis system : Malfunction information displayed on LCD
- HEPA filter and Bacteria filter from Italy. Five-stage filters keeps away most of impurity, bacteria and PM (particulate matter)2.5 microns.
- Light weight 13.9KG only. Compact, easy to store, transport and deliver
- Oxygen Purity : 93%(+3%,-3%)
- Advanced digital flow regulator with an interval of 0.5L/MIN. More accurate than a mechanical flow regulator
- Power On Self-Test and LVD. This conforms with the newest ISO and ensures safety during usage
- Big displacement compressor ensures 30% longer life span, suitable for 24 hours continue running with , service Interval Indicator
- Noise reduction technology \leq 45db
- Re-settable Circuit breaker



Prompt and Efficient Service



Dual Filtration



Years Warranty*



EN ISO
13485:2016

SIZE (cm)

Length

Width

Height



NW



D | M



PCS
/CTN

MAOXY05

31.4

24

51.5

13.9 kg

37.4x30.63.9

1